

# Resene Thinner No.6

## Resene Paints (Australia) Ltd

Version No: 3.5

Safety Data Sheet according to the Health and Safety at Work (Hazardous Substances) Regulations 2017

Initial Date: 27/03/2014

Revision Date: 19/05/2026

Print Date: 19/05/2026

L.GHS.NZL.EN

### SECTION 1 Identification of the substance / mixture and of the company / undertaking

#### Product Identifier

Product name	Resene Thinner No.6
Synonyms	Not Available
Proper shipping name	PAINT RELATED MATERIAL (including paint thinning and reducing compound)
Other means of identification	Not Available

#### Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	6443
--------------------------	------

#### Details of the manufacturer or importer of the safety data sheet

Registered company name	Resene Paints (Australia) Ltd
Address	7 Production Avenue, Molendinar Queensland Australia
Telephone	+61 7 55126600
Fax	+61 7 55126697
Website	<a href="http://www.resene.com.au">www.resene.com.au</a>
Email	<a href="mailto:advice@resene.com.au">advice@resene.com.au</a>

#### Emergency telephone number

Association / Organisation	AUSTRALIAN POISONS CENTRE	CHEMWATCH EMERGENCY RESPONSE (24/7)
Emergency telephone number(s)	131126	+64 800 700 112 (ID#: 9-d44911)
Other emergency telephone number(s)	Not Available	+61 3 9573 3188

### SECTION 2 Hazards identification

#### Classification of the substance or mixture

Classification <sup>[1]</sup>	Flammable Liquids Category 3, Acute Toxicity (Oral) Category 4, Aspiration Hazard Category 1, Acute Toxicity (Dermal) Category 4, Skin Corrosion/Irritation Category 2, Serious Eye Damage/Eye Irritation Category 2, Acute Toxicity (Inhalation) Category 4, Carcinogenicity Category 2, Reproductive Toxicity Category 2, Specific Target Organ Toxicity - Repeated Exposure Category 2
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI
Determined by Chemwatch using GHS/HSNO criteria	3.1C, 6.1D (dermal), 6.1D (inhalation), 6.1D (oral), 6.1E (aspiration), 6.3A, 6.4A, 6.7B, 6.8B, 6.9B

#### Label elements

Hazard pictogram(s)	
Signal word	Danger

#### Hazard statement(s)

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H351	Suspected of causing cancer.
H361	Suspected of damaging fertility or the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure. (Oral, Dermal, Inhalation)

## Resene Thinner No.6

## Precautionary statement(s) Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P260	Do not breathe mist/vapours/spray.
P271	Use only a well-ventilated area.
P280	Wear protective gloves, protective clothing, eye protection and face protection.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/intrinsically safe equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P264	Wash all exposed external body areas thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P202	Do not handle until all safety precautions have been read and understood.

## Precautionary statement(s) Response

P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician/first aider.
P331	Do NOT induce vomiting. If more than 15 mins from Doctor, INDUCE VOMITING (if conscious).
P308+P313	IF exposed or concerned: Get medical advice/ attention.
P370+P378	In case of fire: Use alcohol resistant foam or normal protein foam to extinguish.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider if you feel unwell.
P302+P352	IF ON SKIN: Wash with plenty of water and soap.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P330	Rinse mouth.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.

## Precautionary statement(s) Storage

P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

## Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.
------	--

No further product hazard information.

## SECTION 3 Composition / information on ingredients

## Substances

See section below for composition of Mixtures

## Mixtures

CAS No	%[weight]	Name
1330-20-7	80-90	<u>xylene</u>
100-41-4	10-20	<u>ethylbenzene</u>
<b>Legend:</b>	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L; * EU IOELVs available	

## SECTION 4 First aid measures

## Description of first aid measures

<b>Eye Contact</b>	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> <li>▶ Wash out immediately with fresh running water.</li> <li>▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>▶ Seek medical attention without delay; if pain persists or recurs seek medical attention.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>
<b>Skin Contact</b>	<p>If skin contact occurs:</p> <ul style="list-style-type: none"> <li>▶ Immediately remove all contaminated clothing, including footwear.</li> <li>▶ Flush skin and hair with running water (and soap if available).</li> <li>▶ Seek medical attention in event of irritation.</li> </ul>
<b>Inhalation</b>	If aerosols, sprays, vapours, fumes or combustion products are inhaled, remove affected person from contaminated area. Keep at rest until recovered. If symptoms develop seek medical attention.
<b>Ingestion</b>	<ul style="list-style-type: none"> <li>▶ If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.</li> <li>▶ If swallowed do <b>NOT</b> induce vomiting.</li> </ul>

Continued...

## Resene Thinner No.6

- ▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- ▶ Observe the patient carefully.
- ▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- ▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- ▶ Seek medical advice.
- ▶ Avoid giving milk or oils.
- ▶ Avoid giving alcohol.

**Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

**SECTION 5 Firefighting measures****Extinguishing media**

Foam, dry agent.

**Special hazards arising from the substrate or mixture****Fire Incompatibility**

- ▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

**Advice for firefighters****Fire Fighting**

- ▶ Alert Fire Brigade and tell them location and nature of hazard.

**Fire/Explosion Hazard**

- ▶ Liquid and vapour are flammable.
- Combustion products include:
- ▶ carbon monoxide (CO)
  - ▶ carbon dioxide (CO<sub>2</sub>)
  - ▶ other pyrolysis products typical of burning organic material.

**SECTION 6 Accidental release measures****Personal precautions, protective equipment and emergency procedures**

See section 8

**Environmental precautions**

See section 12

**Methods and material for containment and cleaning up****Minor Spills**

Remove all ignition sources. Contain spill with inert non- combustible absorbent then place in suitable container for disposal. Clean area with large quantity of water to complete clean- up.

**Major Spills**

Remove all ignition sources. Clear area of personnel and move upwind. Wear appropriate personnel protective equipment and clothing to prevent exposure. Avoid breathing in mists or vapours and skin or eyes contact. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non- combustible material onto spillage. Use clean non- sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authority.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

**SECTION 7 Handling and storage****Precautions for safe handling****Safe handling**

- ▶ Containers, even those that have been emptied, may contain explosive vapours.
- Electrostatic discharge may be generated during pumping - this may result in fire.
- ▶ Avoid unnecessary personal contact, including inhalation.
- ▶ **DO NOT allow clothing wet with material to stay in contact with skin**

**Other information**

- ▶ Store in original containers in approved flammable liquid storage area.

**Conditions for safe storage, including any incompatibilities****Suitable container**

- ▶ Packing as supplied by manufacturer.
- ▶ For low viscosity materials (I) : Drums and jerry cans must be of the non-removable head type.

**Storage incompatibility**

Xylenes:

- ▶ may ignite or explode in contact with strong oxidisers
- ▶ attack some plastics, rubber and coatings
- ▶ may generate electrostatic charges on flow or agitation due to low conductivity.
- ▶ Vigorous reactions, sometimes amounting to explosions, can result from the contact between aromatic rings and strong oxidising agents.

For alkyl aromatics:

The alkyl side chain of aromatic rings can undergo oxidation by several mechanisms.

**SECTION 8 Exposure controls / personal protection****Control parameters****Occupational Exposure Limits (OEL)****INGREDIENT DATA**

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
New Zealand Workplace Exposure Standards (WES)	xylene	Dimethylbenzene	50 ppm / 217 mg/m <sup>3</sup>	Not Available	Not Available	Not Available

Continued...

## Resene Thinner No.6

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
New Zealand Workplace Exposure Standards (WES)	ethylbenzene	Ethyl benzene	20 ppm / 88 mg/m <sup>3</sup>	176 mg/m <sup>3</sup> / 40 ppm	Not Available	skin - Skin absorption oto - Ototoxin

## MATERIAL DATA

IFRA Prohibited Fragrance Substance

The International Fragrance Association (IFRA) Standards form the basis for the globally accepted and recognized risk management system for the safe use of fragrance ingredients and are part of the IFRA Code of Practice.

These exposure guidelines have been derived from a screening level of risk assessment and should not be construed as unequivocally safe limits.

Exposed individuals are **NOT** reasonably expected to be warned, by smell, that the Exposure Standard is being exceeded.

for xylenes:

IDLH Level: 900 ppm

Odour Threshold Value: 20 ppm (detection), 40 ppm (recognition)


NOTE: Detector tubes for o-xylene, measuring in excess of 10 ppm, are available commercially.

for ethyl benzene:

Odour Threshold Value: 0.46-0.60 ppm

NOTE: Detector tubes for ethylbenzene, measuring in excess of 30 ppm, are commercially available.

## Exposure controls

Appropriate engineering controls	<b>CARE:</b> Use of a quantity of this material in confined space or poorly ventilated area, where rapid build up of concentrated atmosphere may occur, could require increased ventilation and/or protective gear Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard.
Individual protection measures, such as personal protective equipment	
Eye and face protection	► Safety glasses with side shields.
Skin protection	See Hand protection below
Hands/feet protection	► Wear chemical protective gloves, e.g. PVC. The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer.
Body protection	Overalls
Respiratory protection	Respiratory protection required in insufficiently ventilated working areas and during spraying. An approved respirator with a replaceable vapour/ mist filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements. Reference should be made to AS/NZS 1715 Standard, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716 Standard, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances. Recommended filter type: Type A filter (organic vapour). ► Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content. ► The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate. ► Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

## SECTION 9 Physical and chemical properties

## Information on basic physical and chemical properties

Appearance	Clear colourless liquid with aromatic odour		
Physical state	Liquid	Relative density (Water = 1)	0.87
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	495-516
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	135-155	Molecular weight (g/mol)	Not Available
Flash point (°C)	25	Taste	Not Available
Evaporation rate	0.7	Explosive properties	Not Available
Flammability	Flammable.	Oxidising properties	Not Available
Upper Explosive Limit (%)	12.3	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	1.9	Volatile Component (%vol)	100
Vapour pressure (kPa)	1.893	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	3.7	VOC g/L	870
Heat of Combustion (kJ/g)	Not Available	Ignition Distance (cm)	Not Available

Continued...

## Resene Thinner No.6

Flame Height (cm)	Not Available	Flame Duration (s)	Not Available
Enclosed Space Ignition Time Equivalent (s/m3)	Not Available	Enclosed Space Ignition Deflagration Density (g/m3)	Not Available

## SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	Stable under normal condition of use and storage. Unstable in the presence of incompatible materials.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

## SECTION 11 Toxicological information

## Information on toxicological effects

a) Acute Toxicity	There is sufficient evidence to classify this material as acutely toxic.
b) Skin Irritation/Corrosion	There is sufficient evidence to classify this material as skin corrosive or irritating.
c) Serious Eye Damage/Irritation	There is sufficient evidence to classify this material as eye damaging or irritating
d) Respiratory or Skin sensitisation	Based on available data, the classification criteria are not met.
e) Mutagenicity	Based on available data, the classification criteria are not met.
f) Carcinogenicity	There is sufficient evidence to classify this material as carcinogenic
g) Reproductivity	There is sufficient evidence to classify this material as toxic to reproductivity
h) STOT - Single Exposure	Based on available data, the classification criteria are not met.
i) STOT - Repeated Exposure	There is sufficient evidence to classify this material as toxic to specific organs through repeated exposure
j) Aspiration Hazard	There is sufficient evidence to classify this material as an aspiration hazard

Inhaled	<p>Evidence shows, or practical experience predicts, that the material produces irritation of the respiratory system, in a substantial number of individuals, following inhalation.</p> <p>Inhalation hazard is increased at higher temperatures.</p> <p>Inhalation of vapours may cause drowsiness and dizziness.</p> <p>Acute effects from inhalation of high concentrations of vapour are pulmonary irritation, including coughing, with nausea; central nervous system depression - characterised by headache and dizziness, increased reaction time, fatigue and loss of co-ordination</p> <p>Central nervous system (CNS) depression may include nonspecific discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction time, slurred speech and may progress to unconsciousness.</p> <p>The acute toxicity of inhaled alkylbenzene is best described by central nervous system depression.</p> <p>When humans were exposed to the 100 and 200 ppm for 8 hours about 45-65% is retained in the body.</p> <p>Headache, fatigue, lassitude, irritability and gastrointestinal disturbances (e.g., nausea, anorexia and flatulence) are the most common symptoms of xylene overexposure.</p> <p>Xylene is a central nervous system depressant.</p> <p>Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful.</p>
Ingestion	<p>Swallowing of the liquid may cause aspiration of vomit into the lungs with the risk of haemorrhaging, pulmonary oedema, progressing to chemical pneumonitis; serious consequences may result.</p> <p>Considered an unlikely route of entry in commercial/industrial environments The liquid may produce considerable gastrointestinal discomfort and may be harmful or toxic if swallowed.</p> <p>Accidental ingestion of the material may be damaging to the health of the individual.</p>
Skin Contact	<p>The material may accentuate any pre-existing dermatitis condition</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material</p> <p>Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects.</p> <p>Skin contact with the material may be harmful; systemic effects may result following absorption.</p> <p>The material produces moderate skin irritation; evidence exists, or practical experience predicts, that the material either</p> <ul style="list-style-type: none"> <li>produces moderate inflammation of the skin in a substantial number of individuals following direct contact, and/or</li> <li>produces significant, but moderate, inflammation when applied to the healthy intact skin of animals (for up to four hours), such inflammation being present twenty-four hours or more after the end of the exposure period.</li> </ul>
Eye	<p>Two drops of the ethylbenzene in to the conjunctival sac produced only slight irritation of the conjunctival membrane but no corneal injury.</p> <p>The liquid produces a high level of eye discomfort and is capable of causing pain and severe conjunctivitis.</p> <p>Evidence exists, or practical experience predicts, that the material may cause severe eye irritation in a substantial number of individuals and/or may produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals.</p>
Chronic	<p>On the basis, primarily, of animal experiments, concern has been expressed that the material may produce carcinogenic or mutagenic effects; in respect of the available information, however, there presently exists inadequate data for making a satisfactory assessment.</p> <p>Repeated or long-term occupational exposure is likely to produce cumulative health effects involving organs or biochemical systems.</p> <p>Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems.</p> <p>Toxic: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.</p> <p>Serious damage (clear functional disturbance or morphological change which may have toxicological significance) is likely to be caused by repeated or prolonged exposure.</p> <p>Exposure to the material may cause concerns for human fertility, generally on the basis that results in animal studies provide sufficient evidence to cause a strong suspicion of impaired fertility in the absence of toxic effects, or evidence of impaired fertility occurring at around the same dose levels as other toxic effects, but which are not a secondary non-specific consequence of other toxic effects.</p> <p>Exposure to the material may cause concerns for humans owing to possible developmental toxic effects, generally on the basis that results in appropriate animal studies provide strong suspicion of developmental toxicity in the absence of signs of marked maternal toxicity, or at around the same dose levels as other toxic effects but which are not a secondary non-specific consequence of other toxic effects.</p> <p>Prolonged or repeated contact with xylenes may cause defatting dermatitis with drying and cracking.</p>

## Resene Thinner No.6

Resene Thinner No.6	TOXICITY	IRRITATION
	Not Available	Not Available
xylene	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >1700 mg/kg <sup>[2]</sup>	Eye (Human): 200ppm
	Inhalation (Rat) LC50: 5000 ppm4h <sup>[2]</sup>	Eye (Rodent - rabbit): 5mg/24H - Severe
	Oral (Mouse) LD50; 2119 mg/kg <sup>[2]</sup>	Eye (Rodent - rabbit): 87mg - Mild
		Eye: adverse effect observed (irritating) <sup>[1]</sup>
		Skin (Rodent - rabbit): 100% - Moderate
		Skin (Rodent - rabbit): 500mg/24H - Moderate
		Skin (Rodent - rat): 60uL/8H - Mild
		Skin: adverse effect observed (irritating) <sup>[1]</sup>
ethylbenzene	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: 17800 mg/kg <sup>[2]</sup>	Eye (Rodent - rabbit): 500mg - Severe
	Inhalation (Rat) LC50: 17.2 mg/l4h <sup>[2]</sup>	Skin (Rodent - rabbit): 15mg/24H - Mild
	Oral (Rat) LD50: 3500 mg/kg <sup>[2]</sup>	

**Legend:**

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

Resene Thinner No.6	Asthma-like symptoms may continue for months or even years after exposure to the material ends. Data demonstrate that during inhalation exposure, aromatic hydrocarbons undergo substantial partitioning into adipose tissues.
XYLENE	Reproductive effector in rats The substance is classified by IARC as Group 3: <b>NOT</b> classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing.
ETHYLBENZENE	Liver changes, uterine tract, effects on fertility, foetotoxicity, specific developmental abnormalities (musculoskeletal system) recorded. <b>NOTE:</b> Substance has been shown to be mutagenic in at least one assay, or belongs to a family of chemicals producing damage or change to cellular DNA.  <b>WARNING:</b> This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans.
Resene Thinner No.6 & ETHYLBENZENE	Ethylbenzene is readily absorbed following inhalation, oral, and dermal exposures, distributed throughout the body, and excreted primarily through urine.
XYLENE & ETHYLBENZENE	The material may produce severe irritation to the eye causing pronounced inflammation. The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

Acute Toxicity	✓	Carcinogenicity	✓
Skin Irritation/Corrosion	✓	Reproductivity	✓
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✗
Respiratory or Skin sensitisation	✗	STOT - Repeated Exposure	✓
Mutagenicity	✗	Aspiration Hazard	✓

**Legend:** ✗ – Data either not available or does not fill the criteria for classification  
✓ – Data available to make classification

## SECTION 12 Ecological information

## Toxicity

Resene Thinner No.6	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
xylene	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	4.6mg/l	2
	EC50	48h	Crustacea	1.8mg/l	2
	NOEC(ECx)	73h	Algae or other aquatic plants	0.44mg/l	2
	LC50	96h	Fish	2.6mg/l	2

ethylbenzene

Endpoint	Test Duration (hr)	Species	Value	Source
EC50	72h	Algae or other aquatic plants	2.4-9.8mg/L	4

EC50	48h	Crustacea	1.37-4.4mg/l	4
EC50(ECx)	24h	Algae or other aquatic plants	0.02-938mg/L	4
EC50	96h	Algae or other aquatic plants	1.7-7.6mg/L	4
LC50	96h	Fish	3.381-4.075mg/L	4

**Legend:** *Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. US EPA, Ecotox database - Aquatic Toxicity Data 4. ECETOC Aquatic Hazard Assessment Data 5. NITE (Japan) - Bioconcentration Data 6. METI (Japan) - Bioconcentration Data 7. Vendor Data*

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark.  
For Aromatic Substances Series:  
Environmental Fate: Large, molecularly complex polycyclic aromatic hydrocarbons, or PAHs, are persistent in the environment longer than smaller PAHs.  
For Xylenes:  
log Koc : 2.05-3.08; Koc : 25.4-204; Half-life (hr) air : 0.24-42; Half-life (hr) H2O surface water : 24-672; Half-life (hr) H2O ground : 336-8640; Half-life (hr) soil : 52-672; Henry's Pa m3 /mol : 637-879; Henry's atm m3 /mol - 7.68E-03; BOD 5 if unstated - 1.4,1%; COD - 2.56,13% ThOD - 3.125 : BCF : 23; log BCF : 1.17-2.41.  
For ethylbenzene:  
log Kow, 3.15  
log Koc : 1.98-3.04  
Koc : 164  
log Kom : 1.73-3.23  
Vapour Pressure, 1270 Pa (1.27 kPa)  
Half-life (hr) air : 0.24-85.6  
Half-life (hr) H2O surface water : 5-240  
Half-life (hr) H2O ground : 144-5472  
Half-life (hr) soil : 72-240  
Henry's Pa m3 /mol: 748-887  
Henry's atm m3 /mol: 8.44E-03  
ThOD : 3.17  
BCF : 3.15-146  
log BCF : 1.19-2.67  
**Environmental fate:**  
Ethylbenzene partitions to air from water and soil, and is degraded in air.  
**DO NOT discharge into sewer or waterways.**

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
xylene	HIGH (Half-life = 360 days)	LOW (Half-life = 1.83 days)
ethylbenzene	HIGH (Half-life = 228 days)	LOW (Half-life = 3.57 days)

Bioaccumulative potential

Ingredient	Bioaccumulation
xylene	MEDIUM (BCF = 740)
ethylbenzene	LOW (BCF = 79.43)

Mobility in soil

Ingredient	Mobility
ethylbenzene	LOW (Log KOC = 517.8)


SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal	<ul style="list-style-type: none"><li>Containers may still present a chemical hazard/ danger when empty.</li><li>Legislation addressing waste disposal requirements may differ by country, state and/ or territory.</li><li><b>DO NOT allow wash water from cleaning or process equipment to enter drains.</b></li><li>Recycle wherever possible.</li><li>Consult manufacturer for recycling option.</li></ul> <p>Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package.</p> <p>Flammable substance can be disposed of if the substance is treated by using a method that changes the characteristics or composition of the substance so that the substance is no longer a hazardous substance or exporting the substance from Australia as waste.</p> <p>For treating and discharging processes contact your local authority.</p> <p>The treating may include burning the substance if the burning is managed to ensure that no person, or place where a person may legally be present.</p>
------------------------------	---

SECTION 14 Transport information

Labels Required

	
Marine Pollutant	NO
HAZCHEM	•3Y; •3YE



## Resene Thinner No.6

## Land transport (UN)

14.1. UN number or ID number	1263	
14.2. UN proper shipping name	PAINT RELATED MATERIAL (including paint thinning and reducing compound)	
14.3. Transport hazard class(es)	Class	3
	Subsidiary Hazard	Not Applicable
14.4. Packing group	III	
14.5. Environmental hazard	Not Applicable	
14.6. Special precautions for user	Special provisions	163; 367
	Limited quantity	5 L

## Air transport (ICAO-IATA / DGR)

14.1. UN number	1263	
14.2. UN proper shipping name	PAINT RELATED MATERIAL (including paint thinning and reducing compound)	
14.3. Transport hazard class(es)	ICAO/IATA Class	3
	ICAO / IATA Subsidiary Hazard	Not Applicable
	ERG Code	3L
14.4. Packing group	III	
14.5. Environmental hazard	Not Applicable	
14.6. Special precautions for user	Special provisions	A3 A72 A192
	Cargo Only Packing Instructions	364
	Cargo Only Maximum Qty / Pack	60 L
	Passenger and Cargo Packing Instructions	353
	Passenger and Cargo Maximum Qty / Pack	5 L
	Passenger and Cargo Limited Quantity Packing Instructions	Y341
	Passenger and Cargo Limited Maximum Qty / Pack	1 L

## Sea transport (IMDG-Code / GGVSee)

14.1. UN number	1263	
14.2. UN proper shipping name	PAINT RELATED MATERIAL (including paint thinning and reducing compound)	
14.3. Transport hazard class(es)	IMDG Class	3
	IMDG Subsidiary Hazard	Not Applicable
14.4. Packing group	III	
14.5. Environmental hazard	Not Applicable	
14.6. Special precautions for user	EMS Number	F-E, S-E
	Special provisions	163 367
	Limited Quantities	5 L

## 14.7. Maritime transport in bulk according to IMO instruments

## 14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

## 14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
xylene	Not Applicable
ethylbenzene	Not Applicable

## 14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
xylene	Not Applicable
ethylbenzene	Not Applicable

## SECTION 15 Regulatory information

## Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

Continued...

HSR Number	Group Standard
HSR002669	Surface Coatings and Colourants Flammable Carcinogenic Group Standard 2020
Please refer to Section 8 of the SDS for any applicable tolerable exposure limit or Section 12 for environmental exposure limit.	

**xylene is found on the following regulatory lists**

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

**ethylbenzene is found on the following regulatory lists**

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

**Additional Regulatory Information**  
Not Applicable

**Hazardous Substance Location**  
Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantity (Closed Containers)	Quantity (Open Containers)
3.1C	500 L in containers more than 5 L	250 L
3.1C	1 500 L in containers up to and including 5 L	250 L

**Certified Handler**  
Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

**Maximum quantities of certain hazardous substances permitted on passenger service vehicles**  
Subject to Regulation 13.14 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Gas (aggregate water capacity in mL)	Liquid (L)	Solid (kg)	Maximum quantity per package for each classification
3.1C or 3.1D				10 L

**Tracking Requirements**  
Not Applicable

National Inventory	Status
Australia - AIIIC / Australia Non-Industrial Use	Yes
New Zealand - NZIoC	Yes
UAE - Control List (Banned/Restricted Substances)	
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

**SECTION 16 Other information**

Revision Date	19/05/2026
Initial Date	27/03/2014

Version	Date of Update	Sections Updated
2.5	18/05/2026	Hazards identification - Classification, Accidental release measures - Spills (major)

**Other information**  
The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment.

**Definitions and abbreviations**

- PC - TWA: Permissible Concentration-Time Weighted Average
- PC - STEL: Permissible Concentration-Short Term Exposure Limit
- IARC: International Agency for Research on Cancer
- ACGIH: American Conference of Governmental Industrial Hygienists

**Resene Thinner No.6**

- STEL: Short Term Exposure Limit
- TEEL: Temporary Emergency Exposure Limit,
- IDLH: Immediately Dangerous to Life or Health Concentrations
- ES: Exposure Standard
- OSF: Odour Safety Factor
- NOAEL: No Observed Adverse Effect Level
- LOAEL: Lowest Observed Adverse Effect Level
- TLV: Threshold Limit Value
- LOD: Limit Of Detection
- OTV: Odour Threshold Value
- BCF: BioConcentration Factors
- BEI: Biological Exposure Index
- DNEL: Derived No-Effect Level
- PNEC: Predicted no-effect concentration
- MARPOL: International Convention for the Prevention of Pollution from Ships
- IMSBC: International Maritime Solid Bulk Cargoes Code
- IGC: International Gas Carrier Code
- IBC: International Bulk Chemical Code
  
- AIIC: Australian Inventory of Industrial Chemicals
- DSL: Domestic Substances List
- NDSL: Non-Domestic Substances List
- IECSC: Inventory of Existing Chemical Substance in China
- EINECS: European INventory of Existing Commercial chemical Substances
- ELINCS: European List of Notified Chemical Substances
- NLP: No-Longer Polymers
- ENCS: Existing and New Chemical Substances Inventory
- KECI: Korea Existing Chemicals Inventory
- NZIoC: New Zealand Inventory of Chemicals
- PICCS: Philippine Inventory of Chemicals and Chemical Substances
- TSCA: Toxic Substances Control Act
- TCSI: Taiwan Chemical Substance Inventory
- INSQ: Inventario Nacional de Sustancias Químicas
- NCI: National Chemical Inventory
- FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.