

Resene Thinner No. 11

Resene Paints Ltd

Version No: 1.2

Safety Data Sheet according to the Health and Safety at Work (Hazardous Substances) Regulations 2017

Initial Date: 15/09/2014

Revision Date: 20/03/2026

Print Date: 20/03/2026

L.GHS.NZL.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name	Resene Thinner No. 11
Synonyms	Not Available
Proper shipping name	PAINT RELATED MATERIAL (including paint thinning and reducing compound)
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	3879
--------------------------	------

Details of the manufacturer or importer of the safety data sheet

Registered company name	Resene Paints Ltd
Address	32-50 Vogel Street Wellington New Zealand
Telephone	+64 4 5770500
Fax	+64 4 5773327
Website	www.resene.co.nz
Email	advice@resene.co.nz

Emergency telephone number

Association / Organisation	NZ POISONS (24hr 7days)	CHEMWATCH EMERGENCY RESPONSE (24/7)
Emergency telephone number(s)	0800 764766	+64 800 700 112 (ID#: 9-d25593)
Other emergency telephone number(s)	Not Available	+61 3 9573 3188

SECTION 2 Hazards identification

Classification of the substance or mixture

Classification ^[1]	Flammable Liquids Category 3, Acute Toxicity (Oral) Category 4, Aspiration Hazard Category 1, Skin Corrosion/Irritation Category 2, Serious Eye Damage/Eye Irritation Category 2, Specific Target Organ Toxicity - Single Exposure (Narcotic Effects) Category 3, Hazardous to the Aquatic Environment Long-Term Hazard Category 2
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI
Determined by Chemwatch using GHS/HSNO criteria	3.1C, 6.1D (oral), 6.1E (aspiration), 6.3A, 6.4A, 6.9B (narcotic effects), 9.1B

Label elements

Hazard pictogram(s)	
Signal word	Warning

Hazard statement(s)

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H305	May be harmful if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statement(s) Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
------	--

Resene Thinner No. 11

P271	Use only a well-ventilated area.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/intrinsically safe equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P261	Avoid breathing mist/vapours/spray.
P264	Wash all exposed external body areas thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P273	Avoid release to the environment.
P280	Wear protective gloves, protective clothing, eye protection and face protection.

Precautionary statement(s) Response

P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician/first aider.
P331	Do NOT induce vomiting. If more than 15 mins from Doctor, INDUCE VOMITING (if conscious).
P370+P378	In case of fire: Use alcohol resistant foam or normal protein foam to extinguish.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P391	Collect spillage.
P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider if you feel unwell.
P302+P352	IF ON SKIN: Wash with plenty of water and soap.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P330	Rinse mouth.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.

Precautionary statement(s) Storage

P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.
------	--

No further product hazard information.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
64742-95-6	100	<u>naphtha petroleum, light aromatic solvent</u>
incl. 95-63-6	20-40	<u>1,2,4-trimethyl benzene</u>
incl. 108-67-8	5-10	<u>1,3,5-trimethyl benzene</u>
incl. 98-82-8	0.1-1	<u>cumene</u>
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L; * EU IOELVs available	

SECTION 4 First aid measures

Description of first aid measures

Eye Contact	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> ▶ Wash out immediately with fresh running water. ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▶ Seek medical attention without delay; if pain persists or recurs seek medical attention. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	<p>If skin or hair contact occurs:</p> <ul style="list-style-type: none"> ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation.
Inhalation	<p>If aerosols, sprays, vapours, fumes or combustion products are inhaled, remove affected person from contaminated area. Keep at rest until recovered. If symptoms develop seek medical attention.</p>
Ingestion	<ul style="list-style-type: none"> ▶ If swallowed do NOT induce vomiting. ▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. ▶ Observe the patient carefully. ▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. ▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. ▶ Seek medical advice.

Continued...

Resene Thinner No. 11

- ▶ Avoid giving milk or oils.
- ▶ Avoid giving alcohol.
- ▶ If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically

SECTION 5 Firefighting measures**Extinguishing media**

- ▶ Foam.

Special hazards arising from the substrate or mixture**Fire Incompatibility**

- ▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Advice for firefighters**Fire Fighting**

- ▶ Alert Fire Brigade and tell them location and nature of hazard.

Fire/Explosion Hazard

- ▶ Liquid and vapour are flammable.
- Combustion products include:
- ▶ carbon monoxide (CO)
 - ▶ carbon dioxide (CO₂)
 - ▶ other pyrolysis products typical of burning organic material.
- May emit clouds of acrid smoke

SECTION 6 Accidental release measures**Personal precautions, protective equipment and emergency procedures**

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up**Minor Spills**

Remove all ignition sources. Contain spill with inert non- combustible absorbent then place in suitable container for disposal. Clean area with large quantity of water to complete clean- up.

Major Spills

Remove all ignition sources. Clear area of personnel and move upwind. Wear appropriate personnel protective equipment and clothing to prevent exposure. Avoid breathing in mists or vapours and skin or eyes contact. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non- combustible material onto spillage. Use clean non- sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authority.

- ▶ Clear area of personnel and move upwind.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage**Precautions for safe handling****Safe handling**

- ▶ Containers, even those that have been emptied, may contain explosive vapours.
- ▶ Avoid unnecessary personal contact, including inhalation.

Other information

- ▶ Store in original containers in approved flammable liquid storage area.

Conditions for safe storage, including any incompatibilities**Suitable container**

- ▶ Packing as supplied by manufacturer.
- ▶ For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type.

Storage incompatibility

For alkyl aromatics:
The alkyl side chain of aromatic rings can undergo oxidation by several mechanisms.

- ▶ Vigorous reactions, sometimes amounting to explosions, can result from the contact between aromatic rings and strong oxidising agents.

SECTION 8 Exposure controls / personal protection**Control parameters****Occupational Exposure Limits (OEL)****INGREDIENT DATA**

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
New Zealand Workplace Exposure Standards (WES)	cumene	Cumene	10 ppm / 50 mg/m ³	250 mg/m ³ / 50 ppm	Not Available	skin - Skin absorption

MATERIAL DATA

NOTE P: The classification as a carcinogen need not apply if it can be shown that the substance contains less than 0.01% w/w benzene (EINECS No 200-753-7).

NOTE E: Substances with specific effects on human health that are classified as carcinogenic, mutagenic and/ or toxic for reproduction in categories 1 or 2 are ascribed Note E if they are classified as very toxic (T+), toxic (T) or harmful (Xn).

These exposure guidelines have been derived from a screening level of risk assessment and should not be construed as unequivocally safe limits.

Odour threshold: 0.25 ppm.

For trimethyl benzene as mixed isomers (of unstated proportions)

Odour Threshold Value: 2.4 ppm (detection)

Use care in interpreting effects as a single isomer or other isomer mix.

Continued...

Resene Thinner No. 11


Exposed individuals are **NOT** reasonably expected to be warned, by smell, that the Exposure Standard is being exceeded.

For cumene:

Odour Threshold Value: 0.008-0.132 ppm (detection), 0.047 ppm (recognition)

Exposure at or below the TLV-TWA is thought to prevent induction of narcosis.

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard.
Individual protection measures, such as personal protective equipment	
Eye and face protection	► Safety glasses with side shields.
Skin protection	See Hand protection below
Hands/feet protection	► Wear chemical protective gloves, e.g. PVC. The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer.
Body protection	Overalls
Respiratory protection	<p>Respiratory protection required in insufficiently ventilated working areas and during spraying. An approved respirator with a replaceable vapour/ mist filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements. Reference should be made to AS/NZS 1715 Standard, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716 Standard, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances. Recommended filter type: Type A filter (organic vapour).</p> <p>Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content. The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.</p> <p>Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used</p>

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Clear colourless liquid with petroleum odour		
Physical state	Liquid	Relative density (Water = 1)	0.875
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	507
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	154-181	Molecular weight (g/mol)	Not Available
Flash point (°C)	41	Taste	Not Available
Evaporation rate	Not Available BuAC = 1	Explosive properties	Not Available
Flammability	Flammable.	Oxidising properties	Not Available
Upper Explosive Limit (%)	7.0	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	0.8	Volatile Component (%vol)	100
Vapour pressure (kPa)	0.278	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	4.3	VOC g/L	824
Heat of Combustion (kJ/g)	Not Available	Ignition Distance (cm)	Not Available
Flame Height (cm)	Not Available	Flame Duration (s)	Not Available
Enclosed Space Ignition Time Equivalent (s/m3)	Not Available	Enclosed Space Ignition Deflagration Density (g/m3)	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	Stable under normal condition of use and storage.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7

Continued...

Resene Thinner No. 11

Hazardous decomposition products	See section 5
---	---------------

SECTION 11 Toxicological information

Information on toxicological effects

a) Acute Toxicity	There is sufficient evidence to classify this material as acutely toxic.
b) Skin Irritation/Corrosion	There is sufficient evidence to classify this material as skin corrosive or irritating.
c) Serious Eye Damage/Irritation	There is sufficient evidence to classify this material as eye damaging or irritating
d) Respiratory or Skin sensitisation	Based on available data, the classification criteria are not met.
e) Mutagenicity	Based on available data, the classification criteria are not met.
f) Carcinogenicity	Based on available data, the classification criteria are not met.
g) Reproductivity	Based on available data, the classification criteria are not met.
h) STOT - Single Exposure	There is sufficient evidence to classify this material as toxic to specific organs through single exposure
i) STOT - Repeated Exposure	Based on available data, the classification criteria are not met.
j) Aspiration Hazard	There is sufficient evidence to classify this material as an aspiration hazard

Inhaled	<p>Evidence shows, or practical experience predicts, that the material produces irritation of the respiratory system, in a substantial number of individuals, following inhalation. Inhalation hazard is increased at higher temperatures. Inhalation of vapours may cause drowsiness and dizziness.</p> <p>High inhaled concentrations of mixed hydrocarbons may produce narcosis characterised by nausea, vomiting and lightheadedness. Central nervous system (CNS) depression may include nonspecific discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction time, slurred speech and may progress to unconsciousness. A significant number of individuals exposed to mixed trimethylbenzenes complained of nervousness, tension, anxiety and asthmatic bronchitis. Acute effects from inhalation of high concentrations of vapour are pulmonary irritation, including coughing, with nausea; central nervous system depression - characterised by headache and dizziness, increased reaction time, fatigue and loss of co-ordination The acute toxicity of inhaled alkylbenzene is best described by central nervous system depression.</p>
Ingestion	<p>Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual. Ingestion of petroleum hydrocarbons may produce irritation of the pharynx, oesophagus, stomach and small intestine with oedema and mucosal ulceration resulting; symptoms include a burning sensation in the mouth and throat. Considered an unlikely route of entry in commercial/industrial environments.</p>
Skin Contact	<p>Repeated exposure may cause skin cracking, flaking or drying following normal handling and use. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects.</p> <p>The liquid may be miscible with fats or oils and may degrease the skin, producing a skin reaction described as non-allergic contact dermatitis. The material may accentuate any pre-existing dermatitis condition</p>
Eye	<p>This material causes serious eye irritation.</p> <p>Petroleum hydrocarbons may produce pain after direct contact with the eyes.</p>
Chronic	<p>Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems. On the basis, primarily, of animal experiments, the material may be regarded as carcinogenic to humans. Prolonged or repeated skin contact may cause drying with cracking, irritation and possible dermatitis following. Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems. Repeated or prolonged exposure to mixed hydrocarbons may produce narcosis with dizziness, weakness, irritability, concentration and/or memory loss, tremor in the fingers and tongue, vertigo, olfactory disorders, constriction of visual field, paraesthesias of the extremities, weight loss and anaemia and degenerative changes in the liver and kidney.</p>

Resene Thinner No. 11	TOXICITY	IRRITATION
	Not Available	Not Available
naphtha petroleum, light aromatic solvent	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >1900 mg/kg ^[1]	Eye (Rodent - rabbit): 100uL/24H - Mild
	Inhalation (Rat) LC50: >4.42 mg/L4h ^[1]	Eye: no adverse effect observed (not irritating) ^[1]
	Oral (Rat) LD50: >4500 mg/kg ^[1]	Skin: adverse effect observed (irritating) ^[1]
1,2,4-trimethyl benzene	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >3160 mg/kg ^[2]	Eye: adverse effect observed (irritating) ^[1]
	Inhalation (Rat) LC50: 18 mg/L4h ^[2]	Skin: adverse effect observed (irritating) ^[1]
	Oral (Rat) LD50: 6000 mg/kg ^[1]	

Resene Thinner No. 11

1,3,5-trimethyl benzene	TOXICITY	IRRITATION
	dermal (rat) LD50: >3460 mg/kg ^[1]	Eye (Rodent - rabbit): 500mg/24H - Mild
	Inhalation (Rat) LC50: 24 mg/L4h ^[2]	Eye: adverse effect observed (irritating) ^[1]
	Oral (Rat) LD50: 6000 mg/kg ^[1]	Skin (Rodent - rabbit): 20mg/24H - Moderate
cumene		Skin: adverse effect observed (irritating) ^[1]
	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: 2000 mg/kg ^[2]	Eye (Rodent - rabbit): 500mg/24H - Mild
	Inhalation (Rat) LC50: 39 mg/L4h ^[2]	Eye (Rodent - rabbit): 86mg - Mild
	Oral (Rat) LD50: 1400 mg/kg ^[2]	Eye: no adverse effect observed (not irritating) ^[1]
		Skin (Rodent - rabbit): 100mg/24H - Moderate
		Skin (Rodent - rabbit): 10mg/24H - Mild
		Skin: no adverse effect observed (not irritating) ^[1]
Legend: 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances		

Resene Thinner No. 11	Data demonstrate that during inhalation exposure, aromatic hydrocarbons undergo substantial partitioning into adipose tissues.		
NAPHTHA PETROLEUM, LIGHT AROMATIC SOLVENT	Inhalation (rat) TCLO: 1320 ppm/6h/90D-I * [Devoe] For C9 aromatics (typically trimethylbenzenes - TMBs) Acute Toxicity Acute toxicity studies (oral, dermal and inhalation routes of exposure) have been conducted in rats using various solvent products containing predominantly mixed C9 aromatic hydrocarbons (CAS RN 64742-95-6).		
1,2,4-TRIMETHYL BENZENE	CHEMWATCH 2325 1,3,5-trimethylbenzene		
1,3,5-TRIMETHYL BENZENE	CHEMWATCH 12171 1,2,4-trimethylbenzene The material may be irritating to the eye, with prolonged contact causing inflammation.		
CUMENE	Cumene is reasonably anticipated to be a human carcinogen based on sufficient evidence of carcinogenicity from studies in experimental animals. similar metabolic pathways. The relevance of the kidney tumors to cancer in humans is uncertain; there is evidence that a species-specific mechanism not relevant to humans contributes to their induction, but it is possible that other mechanisms relevant to humans, such as genotoxicity, may also contribute to kidney-tumour formation in male rats. For aromatic terpenes: Acute toxicity: Mammalian LD50 for p-cymene have shown it to have low toxic potential. Tenth Annual Report on Carcinogens: Substance anticipated to be Carcinogen [National Toxicology Program: U.S. Dep. WARNING: This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans.		
Resene Thinner No. 11 & 1,2,4-TRIMETHYL BENZENE & 1,3,5-TRIMETHYL BENZENE & CUMENE	Asthma-like symptoms may continue for months or even years after exposure to the material ends.		
Resene Thinner No. 11 & NAPHTHA PETROLEUM, LIGHT AROMATIC SOLVENT	For Low Boiling Point Naphthas (LBPNs): Acute toxicity: LBPNs generally have low acute toxicity by the oral (median lethal dose [LD50] in rats > 2000 mg/kg-bw), inhalation (LD50 in rats > 5000 mg/m3) and dermal (LD50 in rabbits > 2000 mg/kg-bw) routes of exposure Most LBPNs are mild to moderate eye and skin irritants in rabbits, with the exception of heavy catalytic cracked and heavy catalytic reformed naphthas, which have higher primary skin irritation indices. Studies indicate that normal, branched and cyclic paraffins are absorbed from the mammalian gastrointestinal tract and that the absorption of n-paraffins is inversely proportional to the carbon chain length, with little absorption above C30. For petroleum: This product contains benzene, which can cause acute myeloid leukaemia, and n-hexane, which can be metabolized to compounds which are toxic to the nervous system.		
Resene Thinner No. 11 & NAPHTHA PETROLEUM, LIGHT AROMATIC SOLVENT & 1,2,4-TRIMETHYL BENZENE & 1,3,5-TRIMETHYL BENZENE	For trimethylbenzenes: Absorption of 1,2,4-trimethylbenzene occurs after oral, inhalation, or dermal exposure.		
1,2,4-TRIMETHYL BENZENE & 1,3,5-TRIMETHYL BENZENE	Other Toxicity data is available for CHEMWATCH 12172 1,2,3-trimethylbenzene		
1,3,5-TRIMETHYL BENZENE & CUMENE	The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.		
Acute Toxicity	✓	Carcinogenicity	✗
Skin Irritation/Corrosion	✓	Reproductivity	✗
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✓
Respiratory or Skin sensitisation	✗	STOT - Repeated Exposure	✗
Mutagenicity	✗	Aspiration Hazard	✓

Legend: ✗ – Data either not available or does not fill the criteria for classification
 ✓ – Data available to make classification

SECTION 12 Ecological information

Continued...

Toxicity

Resene Thinner No. 11	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
naphtha petroleum, light aromatic solvent	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	19mg/l	1
	EC50	48h	Crustacea	6.14mg/l	1
	EC50	96h	Algae or other aquatic plants	64mg/l	2
	NOEC(ECx)	72h	Algae or other aquatic plants	1mg/l	1
1,2,4-trimethyl benzene	Endpoint	Test Duration (hr)	Species	Value	Source
	BCF	1344h	Fish	31-207	7
	EC50	48h	Crustacea	ca.6.14mg/l	1
	EC50	96h	Algae or other aquatic plants	2.356mg/l	2
	EC50(ECx)	96h	Algae or other aquatic plants	2.356mg/l	2
	LC50	96h	Fish	3.41mg/l	2
1,3,5-trimethyl benzene	Endpoint	Test Duration (hr)	Species	Value	Source
	BCF	1680h	Fish	23-342	7
	EC50	48h	Crustacea	13mg/L	5
	NOEC(ECx)	384h	Crustacea	0.257mg/l	2
	EC50	96h	Algae or other aquatic plants	3.084mg/l	2
	LC50	96h	Fish	5.216mg/l	2
cumene	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	1.29mg/l	2
	EC50	48h	Crustacea	4mg/l	1
	NOEC(ECx)	96h	Crustacea	0.4mg/l	1
	LC50	96h	Fish	2.7mg/l	2
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. US EPA, Ecotox database - Aquatic Toxicity Data 4. ECETOC Aquatic Hazard Assessment Data 5. NITE (Japan) - Bioconcentration Data 6. METI (Japan) - Bioconcentration Data 7. Vendor Data				

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark.
For Low Boiling Point Naphthas (LBPNS)
Environmental Fate:
Based on the available information, all of these LBPNS are likely to have high proportions of C4-C6 hydrocarbons that are considered to be persistent in air, based on criteria defined in the Persistence and Bioaccumulation Regulations of CEPA 1999.
When spilled this product may act as a typical oil, causing a film, sheen, emulsion or sludge at or beneath the surface of the body of water.
For 1,2,4 - Trimethylbenzene:
Half-life (hr) air: 0.48-16;
Half-life (hr) H2O surface water: 0.24 -672;
Half-life (hr) H2O ground: 336-1344;
Half-life (hr) soil: 168-672;
Henry's Pa m3 /mol: 385 -627;
Bioaccumulation: not significant.
For Aromatic Substances Series:
Environmental Fate: Large, molecularly complex polycyclic aromatic hydrocarbons, or PAHs, are persistent in the environment longer than smaller PAHs.
For petroleum distillates:
Environmental fate:
When petroleum substances are released into the environment, four major fate processes will take place: dissolution in water, volatilization, biodegradation and adsorption.
For C9 aromatics (typically trimethylbenzene - TMBs)
Chemicals in this category possess properties indicating a hazard for the environment (acute toxicity for fish, invertebrates, and algae from 1 to 10 mg/L).
DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
1,2,4-trimethyl benzene	LOW (Half-life = 56 days)	LOW (Half-life = 0.67 days)
1,3,5-trimethyl benzene	HIGH	HIGH
cumene	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation
1,2,4-trimethyl benzene	LOW (BCF = 275)
1,3,5-trimethyl benzene	LOW (BCF = 342)
cumene	LOW (BCF = 35.5)

Mobility in soil

Resene Thinner No. 11

Ingredient	Mobility
1,2,4-trimethyl benzene	LOW (Log KOC = 717.6)
1,3,5-trimethyl benzene	LOW (Log KOC = 703)
cumene	LOW (Log KOC = 817.2)

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal	<p>Containers may still present a chemical hazard/ danger when empty.</p> <p>Legislation addressing waste disposal requirements may differ by country, state and/ or territory.</p> <p>DO NOT allow wash water from cleaning or process equipment to enter drains.</p> <p>Recycle wherever possible. Contact manufacturer for recycling option.</p>
------------------------------	--

Disposal Requirements

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package.

Do not allow product or wash water from cleaning or process equipment to enter drains or watercourses. It may be necessary to collect all wash water for treatment before disposal.

The generation of waste should be avoided or minimised wherever possible.

Disposal of this product should comply with Hazard Substances (Disposal) Notice 2017 (EPA Consolidation 30 April 2021) and local regulations.

Flammable substance can be disposed of if the substance is treated by using a method that changes the characteristics or composition of the substance so that the substance is no longer a hazardous substance or exporting the substance from New Zealand as waste.



For treating and discharging processes contact your local authority.

The treating may include burning the substance if the burning is managed to ensure that no person, or place where a person may legally be present.

The substance may be discharged into the environment as waste or disposed into a landfill if the substance will not come into contact with oxidising substances and where is in ignition source which is capable to ignite the substance.

SECTION 14 Transport information

Labels Required

	
Marine Pollutant	
HAZCHEM	•3Y

Land transport (UN)

14.1. UN number or ID number	1263				
14.2. UN proper shipping name	PAINT RELATED MATERIAL (including paint thinning and reducing compound)				
14.3. Transport hazard class(es)	<table> <tr> <td>Class</td><td>3</td></tr> <tr> <td>Subsidiary Hazard</td><td>Not Applicable</td></tr> </table>	Class	3	Subsidiary Hazard	Not Applicable
Class	3				
Subsidiary Hazard	Not Applicable				
14.4. Packing group	III				
14.5. Environmental hazard	Environmentally hazardous				
14.6. Special precautions for user	<table> <tr> <td>Special provisions</td><td>163; 367</td></tr> <tr> <td>Limited quantity</td><td>5 L</td></tr> </table>	Special provisions	163; 367	Limited quantity	5 L
Special provisions	163; 367				
Limited quantity	5 L				

Air transport (ICAO-IATA / DGR)

14.1. UN number	1263								
14.2. UN proper shipping name	PAINT RELATED MATERIAL (including paint thinning and reducing compound)								
14.3. Transport hazard class(es)	<table> <tr> <td>ICAO/IATA Class</td><td>3</td></tr> <tr> <td>ICAO / IATA Subsidiary Hazard</td><td>Not Applicable</td></tr> <tr> <td>ERG Code</td><td>3L</td></tr> </table>	ICAO/IATA Class	3	ICAO / IATA Subsidiary Hazard	Not Applicable	ERG Code	3L		
ICAO/IATA Class	3								
ICAO / IATA Subsidiary Hazard	Not Applicable								
ERG Code	3L								
14.4. Packing group	III								
14.5. Environmental hazard	Environmentally hazardous								
14.6. Special precautions for user	<table> <tr> <td>Special provisions</td><td>A3 A72 A192</td></tr> <tr> <td>Cargo Only Packing Instructions</td><td>364</td></tr> <tr> <td>Cargo Only Maximum Qty / Pack</td><td>60 L</td></tr> <tr> <td>Passenger and Cargo Packing Instructions</td><td>353</td></tr> </table>	Special provisions	A3 A72 A192	Cargo Only Packing Instructions	364	Cargo Only Maximum Qty / Pack	60 L	Passenger and Cargo Packing Instructions	353
Special provisions	A3 A72 A192								
Cargo Only Packing Instructions	364								
Cargo Only Maximum Qty / Pack	60 L								
Passenger and Cargo Packing Instructions	353								

Continued...

	Passenger and Cargo Maximum Qty / Pack	5 L
	Passenger and Cargo Limited Quantity Packing Instructions	Y341
	Passenger and Cargo Limited Maximum Qty / Pack	1 L

Sea transport (IMDG-Code / GGVSee)

14.1. UN number	1263	
14.2. UN proper shipping name	PAINT RELATED MATERIAL (including paint thinning and reducing compound)	
14.3. Transport hazard class(es)	IMDG Class	3
	IMDG Subsidiary Hazard	Not Applicable
14.4. Packing group	III	
14.5. Environmental hazard	Marine Pollutant	
14.6. Special precautions for user	EMS Number	F-E, S-E
	Special provisions	163 367
	Limited Quantities	5 L

14.7. Maritime transport in bulk according to IMO instruments

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
naphtha petroleum, light aromatic solvent	Not Applicable
1,2,4-trimethyl benzene	Not Applicable
1,3,5-trimethyl benzene	Not Applicable
cumene	Not Applicable

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
naphtha petroleum, light aromatic solvent	Not Applicable
1,2,4-trimethyl benzene	Not Applicable
1,3,5-trimethyl benzene	Not Applicable
cumene	Not Applicable

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard
HSR002662	Surface Coatings and Colourants Flammable Group Standard 2020

Please refer to Section 8 of the SDS for any applicable tolerable exposure limit or Section 12 for environmental exposure limit.

naphtha petroleum, light aromatic solvent is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List
New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals
New Zealand Inventory of Chemicals (NZIoC)
New Zealand Land Transport Rule; Dangerous Goods 2005 - Schedule 2 Dangerous Goods in Limited Quantities and Consumer Commodities

1,2,4-trimethyl benzene is found on the following regulatory lists

New Zealand Approved Hazardous Substances with controls
New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals
New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data
New Zealand Inventory of Chemicals (NZIoC)
New Zealand Land Transport Rule; Dangerous Goods 2005 - Schedule 2 Dangerous Goods in Limited Quantities and Consumer Commodities

1,3,5-trimethyl benzene is found on the following regulatory lists

New Zealand Approved Hazardous Substances with controls
New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals
New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data
New Zealand Inventory of Chemicals (NZIoC)

cumene is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans
New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals
New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data
New Zealand Inventory of Chemicals (NZIoC)
New Zealand Workplace Exposure Standards (WES)

Not Applicable

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantity (Closed Containers)	Quantity (Open Containers)
3.1C	500 L in containers more than 5 L	250 L
3.1C	1 500 L in containers up to and including 5 L	250 L

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

Subject to Regulation 13.14 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Gas (aggregate water capacity in mL)	Liquid (L)	Solid (kg)	Maximum quantity per package for each classification
3.1C or 3.1D				10 L

Not Applicable

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
New Zealand - NZIoC	Yes
Legend:	<p><i>Yes = All CAS declared ingredients are on the inventory</i></p> <p><i>No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.</i></p>

Revision Date	20/03/2026
Initial Date	15/09/2014

Version	Date of Update	Sections Updated
0.2	19/03/2026	Hazards identification - Classification

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment.

- ▶ PC - TWA: Permissible Concentration-Time Weighted Average
- ▶ PC - STEL: Permissible Concentration-Short Term Exposure Limit
- ▶ IARC: International Agency for Research on Cancer
- ▶ ACGIH: American Conference of Governmental Industrial Hygienists
- ▶ STEL: Short Term Exposure Limit
- ▶ TEEL: Temporary Emergency Exposure Limit,
- ▶ IDLH: Immediately Dangerous to Life or Health Concentrations
- ▶ ES: Exposure Standard
- ▶ OSF: Odour Safety Factor
- ▶ NOAEL: No Observed Adverse Effect Level
- ▶ LOAEL: Lowest Observed Adverse Effect Level
- ▶ TLV: Threshold Limit Value
- ▶ LOD: Limit Of Detection
- ▶ OTV: Odour Threshold Value
- ▶ BCF: BioConcentration Factors
- ▶ BEI: Biological Exposure Index
- ▶ DNEL: Derived No-Effect Level
- ▶ PNEC: Predicted no-effect concentration
- ▶ MARPOL: International Convention for the Prevention of Pollution from Ships
- ▶ IMSBC: International Maritime Solid Bulk Cargoes Code
- ▶ IGC: International Gas Carrier Code

Continued...

Resene Thinner No. 11

- ▶ IBC: International Bulk Chemical Code
- ▶ AIIC: Australian Inventory of Industrial Chemicals
- ▶ DSL: Domestic Substances List
- ▶ NDSL: Non-Domestic Substances List
- ▶ IECSC: Inventory of Existing Chemical Substance in China
- ▶ EINECS: European INventory of Existing Commercial chemical Substances
- ▶ ELINCS: European List of Notified Chemical Substances
- ▶ NLP: No-Longer Polymers
- ▶ ENCS: Existing and New Chemical Substances Inventory
- ▶ KECI: Korea Existing Chemicals Inventory
- ▶ NZIoC: New Zealand Inventory of Chemicals
- ▶ PICCS: Philippine Inventory of Chemicals and Chemical Substances
- ▶ TSCA: Toxic Substances Control Act
- ▶ TCSI: Taiwan Chemical Substance Inventory
- ▶ INSQ: Inventario Nacional de Sustancias Químicas
- ▶ NCI: National Chemical Inventory
- ▶ FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.