

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase. Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

# Resene

## Anti-Slip Grip Additive

### non-skid, slip-resistant finish

net contents 1 kg  
(enough to mix with 4 litres)



LL8431001F 6-25

**SAFETY PRECAUTIONS**

Read label before use. This material is quite bland, with occasional skin contact and even minor ingestion having negligible hazard. Repeated skin contact may, and any eye contact will, cause irritation.

**PRECAUTIONS**

Store in original labelled container, tightly closed, away from foodstuffs. Avoid release to the environment.

**FIRST AID**

IF SWALLOWED: Rinse mouth. Call a POISONS CENTRE, doctor or first aider if you feel unwell.

IF ON SKIN (or hair): Rinse skin with plenty of water. If skin irritation or rash occurs get medical advice or attention.

IF IN EYES: Rinse cautiously with water for several minutes. If eye irritation persists, get medical advice or attention.

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. If breathing is difficult get prompt medical attention.

If medical advice is required, have product container or label at hand. Further information can be obtained from

AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383.  
 NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

**SPILLS** Collect using dustless method (vacuum or wet method). Wear appropriate protective clothing. Collect in a properly labelled container for reuse or dispose. Refer to local waste management authority

**Add Resene Anti-Slip Grip Additive to pigmented or clear Resene flooring or foot trafficable coatings for wet slip resistance to meet the requirements of the NZ Building Code and AS 4586:2013. See the Resene website, [resene.com/anti-slip](http://resene.com/anti-slip) for substrates and application rates of tested systems.**

**Dose**

- Add 250 g of Resene Anti-Slip Grip Additive per litre of paint. Lower dose rates will provide less slip resistance.
- Do not exceed the specified dose rate as this may have adverse effects on the product's characteristics. If in doubt, trial a small patch before painting the entire area.

**Mixing**

- Use a large mixing container, as the addition of Resene Anti-Slip Grip Additive will increase the total paint volume by approximately 20%.
- Add to the Resene paint, or for a two-pack product, add to the Base or add after the Base and Hardener have been thoroughly mixed and thinned.
- Mix thoroughly with a stirrer until perfectly homogeneous. **Do not shake.**
- Settling may occur upon standing. Stir regularly during application to ensure the mixture is uniform.

**Application**

- Prep and prime the surface with the recommended substrate primer. Then apply the mixed product evenly by roller. Do not apply below the temperature recommended for the topcoat.
- For exterior two coat systems, apply one coat of

Resene Anti-Slip Grip Additive modified coating followed by a second coat of unmodified product.

- For interior three coat flooring systems, add Resene Anti-Slip Grip Additive to the second coat.
- Allow extra time before recoating due to the thicker film.
- Resene Anti-Slip Grip Additive will alter the appearance of the finish providing a surface with a micro-texture. A slight black fleck will be visible when Resene Anti-Slip Grip Additive is used in clear finishes.

**Typical coverage**

- The coverage of the grit modified coating can be up to 50% less than unmodified product. Allow for this when estimating the quantity you will need.

**Enjoy the Resene Promise of quality on premium paints.** See your Resene ColorShop or the Resene website for a copy.

Read the appropriate Safety Data Sheet before use.

**Please ensure that use of this product is compatible with the substrate and surface preparation method. Resene does not accept any responsibility for the application of incorrect product to substrate. Resene products are designed to be used as a system for optimal results. Substitution may cause substandard results or system failure. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.**



Anti-Slip Grip Additive SDS

# Resene

the paint the professionals use

In Australia: Resene Paints (Aust) Ltd  
 7 Production Ave, PO Box 918, Ashmore City, QLD 4214  
 Ph 1800 738 383 Visit [resene.com.au](http://resene.com.au)

In New Zealand: Resene Paints Ltd  
 Vogel St, PO Box 38242, Wgtn Mail Centre, Lower Hutt 5045  
 Ph (04) 577 0500. Visit [resene.co.nz](http://resene.co.nz)