

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase. Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

**WARNING**

**KEEP OUT OF REACH OF CHILDREN**



**Resene**

**Wintergrade Additive**

**to help waterborne Resene paint  
cure in the cold**



**net  
contents  
1 litre**

LL8172001F 7/19

**SAFETY PRECAUTIONS**

Read label before use. Keep out of reach of children. Causes skin irritation. Causes serious eye irritation. Harmful to aquatic life.

**PRECAUTIONS**

**DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT.**

Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Wear protective gloves and clothing, eye and face protection. Avoid release to the environment.

**FIRST AID**

**IF SWALLOWED:** Call a POISON CENTRE, doctor or first aider if you feel unwell.

**IF ON SKIN (or hair):** Wash with plenty of soap and water. If skin irritation occurs get medical advice. Take off contaminated clothing and wash before reuse.

**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists get medical advice or attention.

When seeking medical advice take this container with you.

Further information can be obtained from  
AUST: POISONS INFORMATION CENTRE 131 126  
or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

**SPILLS** Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to run off into waterways. Refer to local waste management authority.

**Resene Wintergrade Additive is an additive for waterborne coatings providing extra protection against paint application in colder temperatures, so you can apply treated paint in temperatures down to 3°C.**

**Cold conditions can cause standard waterborne paint films to crack or powder and lead to premature paint failure. When using paint over winter, keep an eye on the temperature, both on the surface and in the air.**

**Remember a surface can be a lot colder than the air that surrounds it so you may find it's best to change your order of work and work on surfaces like plasterboard in the early morning and move to areas like concrete, which tend to be cooler in cold weather until they have had a chance to warm up a little.**

**Instructions for use**

• Always shake Resene Wintergrade Additive before use.

• Add 2% of Resene Wintergrade Additive to Resene waterborne paint:

+ 10ml for a 500ml can

+ 20ml for a 1L can

+ 40ml for a 2L can

+ 80ml for a 4L can

+ 200ml for a 10L pail

One capful = 15ml.

• Do not add excessive amounts of Resene Wintergrade Additive - higher than recommended dosage does not provide additional benefit and may impact product performance.

• Do not use with any other Resene additive, Resene waterborne alkyds or waterborne enamels. Resene X-200 may need a small addition of water to ease flow.

• Addition and mixing should be conducted outdoors or in well ventilated areas only.

• Thoroughly mix Resene Wintergrade Additive into paint and begin painting following the instructions for the Resene paint you are using.

**USE THE TREATED PAINT WITHIN 10 WORKING DAYS. TREATED PAINT WILL THICKEN WHEN STORED FOR LONGER PERIODS AND WILL BECOME UNUSABLE.**

**Suitable for exterior or interior use.**

Only use in cool conditions less than 10°C. If the temperature is higher, use standard Resene paints without Resene Wintergrade Additive.



**In every case it is recommended that the appropriate Safety Data Sheet is consulted prior to application.**

**In Australia:**

Resene Paints (Aust) Limited  
7 Production Ave, PO Box 924, Beenleigh, Qld 4207  
Ph 1800 738 383 Visit [www.resene.com.au](http://www.resene.com.au)

# Resene

the paint the professionals use

**In New Zealand:**

Resene Paints Ltd  
Vogel St, PO Box 38242, Wgtn Mail Centre, Lower Hutt 5045  
Ph (04) 577 0500 Visit [www.resene.co.nz](http://www.resene.co.nz)